

## DIRCPL-6-1-1000-A-XX Directional Coupler, 6 dB, Power Splitter / Combiner; Hybride





#### Features

- Directional coupler
- 6 dB Power splitter / combiner
- Frequency range : 1 1000 MHz
- Coupling : 6 dB
- Insertion loss : 6 dB
- High isolation
- 3 SMA ports
- Very low return loss
- Solid aluminium case
- RoHS compliant

#### Applications

- Directional coupler
- Combining and splitting power
- Radio-frequency applications
- Test equipment
- HAM radio
- HF, VHF and UHF bands

#### **General description**

This three port device samples incident or reflected power without disturbing the transmission line (P1–P3).

It has a flat insertion loss and coupling. Isolation is > 40 dB over the entire operating range. Port 1 (DUT) has a very low return loss, which keeps measurements errors due to impedance mismatch low.

This device can also be used as 6 dB power splitter / combiner with a very high isolation.

The unit is designed for 50 ohm systems. It is housed in a milled aluminium enclosure.



# Specifications

General				
Item	Value	Tolerance	Dimension	
Maximum signal power	23	-	dBm	
Number of (female) SMA connector ports	3	-	-	
Box weight DIRCPL-6-1-1000-A	0.056 (YF-01) 0.053 (NF-01)		kg	
Outer dimensions (width x depth x height)	35 x 35 x 20	0.1	mm	

#### Versions

Туре	Feature	
DIRCPL-6-1-1000-A- <b>NF</b>	Box without mounting flange	
DIRCPL-6-1-1000-A-YF	Box with mounting flange	



#### **S**-parameters





## S-parameters (continued)





## S-parameters (continued)





#### **Enclosure Drawings**



Note1 : All measures in mm. Tolerance : 0.1 mm.

Note2 : Drawing shows the DIRCPL-6-1-1000-A-YF version only. However, all dimension for the version DIRCPL-6-1-1000-A-NF are identical with the exception of the mounting flanges at the bottom side of the box, which don't exist in the '-NF version.

# **G**quipment

## **Revision history**

Revision	Status	Date
007	Released	March 15, 2024

#### Legal

Specifications are subject to change without notice.

www.gquipment.com